

# Luxury Interior Paint

**Zydex**<sup>®</sup>  
Innovating for Sustainability



## Marvella

Marvella is a luxury interior paint with a pleasant sheen that results in a soft glow on your walls. The paint has a soft hand feel with a smooth lustrous finish. It is a highly washable paint with excellent stain release properties with even the toughest of stains. The innovative binder technology eliminates patchiness during application and provides an odourless experience for the occupier of the space. It is available in an extremely wide range of colours.

### FEATURES

- Pleasant Soft Sheen
- Low Odour, Low VOC
- Seamless Finish
- Excellent Stain Resistance
- Anti-Fungal
- Bright Colours
- Highly Washable
- Wide Variety of Colours

Toll Free:  
1-800-12300-7666

[www.zydexpaints.com](http://www.zydexpaints.com)

# Marvella

## MARVELLA APPLICATION GUIDELINE

### Substrate Preparation

The substrate must be sound, solid, dry, clean and free of dust and grease. Substrate and air temperature during application and drying > 5°C. Marvella must be applied using either brush or roller suitable for interior painting. In case of fresh surface, level the surface using either white cement or acrylic based putty. Apply 1 coat of Zydex Premium Wall Primer before proceeding with painting. In case of repainting, sand down the existing paint to roughen the surface and clean it to ensure it is free of debris. All defects and cracks should be filled using suitable repair compound. Apply 1 coat of Zydex Premium Wall Primer. Painting with Marvella may now proceed. Marvella is not suitable for painting over metal, wood, varnishes and oil based paints.

### Application

Marvella must be applied in principle as a two coat system diluted with water between 20 to 30 percent. A minimum gap of 4 hours must be observed between subsequent coats. Cover all surfaces which are not to be painted. Please ensure that at no point is Marvella diluted beyond 30 percent as this may severely affect the end film properties.

### Consumption

Approximately 7.5 m<sup>2</sup> /ltr (80 sq.ft./ltr) for 2 coats.

Consumption guideline is quoted for smooth surfaces with normal absorbency. Actual consumption may vary based on surface characteristics and is the responsibility of the applicator.

### Cleaning of Equipment

Clean immediately with water after use.

### Packaging and Storage

1 ltr, 4 ltr and 20 ltr.

Shelf life approximately 48 months in a cool shaded area. All unused paint must be packed in smaller air-tight containers to maintain minimum air volume.

### Specifications

Density: 1.20 - 1.50 g/cm<sup>3</sup>

Gloss at 85°: 15-20

Flash Point: NA

Version No. VNT2/17/2024