

Acrylic Based Sealing, Bonding & Admixture Agent

Zydex[®]
Innovating for Sustainability



ZYC **PRIME** + **ACRYLIC SEALER & BONDER**

ZycoPrime is an acrylic co-polymer emulsion supplied as a ready to use bonding agent with superior wet adhesion and universal compatibility. It is also a versatile latex that can be used as a cement modifier for spalled concrete slabs, overhangs, beams, columns and floors. It is also used as a bonding primer and porosity filler with ZycoSil+ during waterproofing applications.

FEATURES

- ✓ Sealing & Bonding Agent
- ✓ Multipurpose & Economical
- ✓ Excellent Wet Adhesion
- ✓ Universal Compatibility
- ✓ Excellent Bonding to Cementitious Concrete & Plaster Surfaces
- ✓ High-performance Cement Admixture

Toll Free:
1-800-12300-7666

www.zydexpaints.com

DESCRIPTION

ZycoPrime+ is an Acrylic Co-polymer emulsion, supplied as a ready to use bonding agent in liquid consistency. It is used as a bonding primer and porosity filler during waterproofing application with ZycoSil+ solution.

FEATURES & BENEFITS

- Multipurpose, UV stable & Economical
- When used in concrete / plaster, it prevents cracking
- It reduces drying and shrinkage cracks
- Reduces permeability of water
- Improves workability of concrete / plaster
- Bonds strongly with concrete, plasters, cementitious surfaces
- Reduces viscosity of cement-injection grout and tile adhesives for better fluidity & bonding

APPLICATION AREAS

- **Waterproofing Membrane** : Roof terraces, sunken portion of toilets & bathrooms, balcony, etc.
- **Concrete Repairs** : Spalled concrete of slabs, chhajas, beams, columns, parapet, floor, etc.
- **Waterproofing &/or Bonding Primer** : Walls & slabs

APPLICATION METHOD

Clean the surface with wire brush or scrubber to remove hidden dirt, loose particles, laitance and dust. Use air blower to clean the surface. De-grease the surface by using suitable solvents if needed.

Always use ZycoPrime+ with ZycoSil+ solution, for seepage proofing.

- **Bonding Primer**
To be used as a clear bonding primer by diluting 1 : 5 with water. Apply on the walls before painting or during putty rendering.
- **Waterproofing Primer**
For priming of masonry substrate, the surface should be thoroughly saturated with ZycoSil+ solution (Dilution Ratio - 1 part ZycoSil+ : 20 parts potable Water : 2 parts of ZycoPrime+).
- **Waterproofing Membrane**
For a waterproofing coating mix 1 part ZycoPrime+ with 1 part of cement & 1 part of 100 mesh sand.
Add water for brushability.
Brush apply the mix in span of 4-6 hours on the prepared concrete substrate. It is recommended to saturate the surface with ZycoSil+ solution prior to this application.
Overlay the coating with a protective screed to the desired slope and thickness.
Coverage : 4-5 m² for a 0.2 mm (200 microns) coat.

- **Repair Mortar & Renders, Floor Screed & PCC**

Prepare the Mortar in the following proportion:

- Cement 50 kg
- 6 mm Down size aggregates 75 kg
- Water 10 litres
- Washed Sand 75 kg
- ZycoPrime+ 6-7.5 litres

For PCC & Plaster work : ZycoPrime+ 100 ml per bag cement
(conforms to IS 2645 - 2003)

SPECIFICATIONS

Form : Milky White, Free flowing Liquid
Specific Gravity : 1.01 to 1.02
Solid content : 35 ± 1%
Viscosity @ 25°C : <500 cps

pH @ 25°C : 6 to 7
Diluent : Clean Potable Water TDS < 1000 ppm
Flash Point : Non Flammable

APPLICATION DETAILS

Sr. No	APPLICATION	RECIPE	ZYCOPRIME+ QTY
1	Patching & Repair Mortar	Portland Cement : 50 kg Washed Sand : 10 KG Water : 10 ltrs	6 - 7.5 ltrs
2	PCC / Plaster*	Portland Cement : 50 kg	100 ml
3	Waterproofing membrane (rough)	Portland Cement : 1 kg Washed Sand : 1 KG	1 ltr
4	Putty	Putty - 20 kg	125 ml
5	Waterproofing Primer	ZycoSil+ solution (1:20)	2 ltr
6	Bonding Primer	5 ltrs water	1 ltr
7	Coving	ZycoPrime+ : 1 ltr Water : 2.5 ltrs Cement : 5 kg Sand : 15 kg Mix manually / mechanically Use the mixture for smooth coving	

* conforms to IS 2645 - 2003

COVERAGE

Vertical Surfaces (Concrete, Brick & Stone) : Approx. 60-100m² (645-1075 ft²) per 2 litres of ZycoPrime+ diluted in a 21 litre solution of 1:20 ZycoSil+ solution in water.

Horizontal Concrete Surfaces : Approx. 24-40m² (260-430 ft²) 2 litre of ZycoPrime+ diluted in a 21 litre solution of 1:20 ZycoSil+ solution in water.

The coverage may vary depending upon permeability of the substrate and surface absorptivity.

PACKING

250ml, 1, 5, 20ltr & 35 ltr.

STORAGE

Store Between +5°C and +45°C.

SHELF LIFE

4 years if stored as recommended.

ABOUT ZYDEX

Established in 1997, Zydex is a specialty chemicals company with the purpose of innovating for sustainability.

Beyond construction products, Zydex offers a diverse set of chemical technologies for the textile, agriculture and pavement industries. We were recently recognised as one of the 25 Most Innovative Companies in India by the Confederation of Indian Industry (CII).


Sustainable Green Chemistry

Zydex is deeply committed to sustainable chemistries that ensure a greener future for everyone. Our commitment has made us a pioneer in introducing non-polluting and non-hazardous technologies that conserve, protect and enhance the environment. Pursuing chemical innovations that would mean a greener, purer and more resource renewable world is our passion. Our technologies have been recognized for their contribution to sustainability and globally accepted.



25 Most Innovative Companies of India

GLOBAL PRESENCE



Version No. VNT2/16/2024